



GENERAL INFORMATION

FIXING & SEALING

SEALING AND FASTENING SYSTEMS.

DEC International delivers various tapes to support the product assortment of flexible ducts. The tapes have been composed from different raw materials to ensure that the tape you need can be delivered by DEC International. The tapes should be applied to dust-free and fat-free surfaces to get a good adhesion. DEC also offers a wide choice of products for sealing various components of air conditioning- and air supply systems. The operating pressure has been measured under laboratory circumstances at a 20°C temperature. The information below is only informative. DEC International disclaims all responsibility of misinterpreting the data. To select the appropriate product within the **SEALING AND FASTENING** group consult the table below

TAPES

Type	Temp. range (°C)	Max. Operating pressure (Pa) at + 20°C	Adhesion ¹⁾	Max. adhesion after/per	Application ²⁾	Fire resistance according to
ASB	-20 - +70	+2000	2.0 kg/cm	24 hours	▲▼	DIN 4102, B2
PSB	-20 - +60	+4000	3.6 kg/cm	24 hours	▲	DIN 4102, B2
ALU	-10 - +90	+1000	38 N/2.5 cm	immediately	▲▼	BS476 Part 7, klasse 1
ALU-R	-10 - +90	+1000	38 N/2.5 cm	immediately	▲▼	BS476 Part 7, klasse 1
PVC	-18 - +90	+1000	0.4 kg/2.5 cm	immediately	▲	-
Duct tape	-20 - +75	+1500	0.55 kg/ cm	immediately	▲▼	-

SEALING MATERIALS

Type	Temp. range (°C)	Max. Operating pressure (Pa)	Adhesion ¹⁾	Drying time	Application ²⁾	Fire resistance according to
GT	-30- +80	irrelevant	1.0 kg/2.5 cm	immediately	▲▼	DIN 4102, B3
SDS	-25- +75	+2500	-	immediately	▲	CSTB, class M1
WDS	-30- +80	+2500	-	48 hours	▲	-

1) the surface has been specified on the information page:

2) application - ▲ = inside use - ▼ = outside use

DEC International offers you a large number of fastening articles for a wide range of purposes. All products within the **FASTENING** product group are intended for mounting ducts and flexible ducts. This product group also contains a number of products on behalf of the fastening of flexible ducts to round, rectangular and oval connections. The support clamps are particularly suitable for suspending heavier weights, e.g. air conditioning units.

FASTENING PRODUCTS

Type	diameter / size	material
Flexible connection "DEC Connector" Sendzimir galv. steel or stainless steel with: • Silicone • Polyurethane • Neoprene • Vinyl	variable	Sendzimir galv. steel or stainless steel (316 Ti) with: • silicone • polyurethane • neoprene • vinyl
Metal clamp	variable, 50 - 660 mm	• strip: stainless steel • clamp: galvanized steel
Multiband/clamps	variable, until 30 metres	• strip: stainless steel • clamp: galvanized steel
Nylon Quick Clamps	variable, 0 - mm	• Nylon
Spiral clamps	fixed, 80 - 400 mm	• Sendzimir galv. steel
Self drilling screws	13 - 50 mm	• Galvanized steel
Self-adhesive pins	19 - 140 mm	• Galvanized steel
Welding pins	25 - 105 mm	• Galvanized steel
Support clamps	M6 up to and incl. M12	• Galvanized steel
Threaded rods	M6 up to and incl. M12	• Galvanized steel
Suspension strap • Type PP • Type PZ	width 19 mm width 17 mm	• copolymer coated galv. Steel • galvanized steel

LIABILITY:

The information contained in this brochure was current on the publication date. DEC INTERNATIONAL reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact DEC INTERNATIONAL checking for any changes in materials and/or information after this brochure was published.

PLEASE NOTICE:

The consultant is responsible for the actual installation and mounting of the product. The mentioned values with respect to temperatures are not appropriate to be used to determine the physical properties. These properties are also dependent on humidity and the temperature of the air inside and outside of the H.V.A.C. system.

TRADEMARKS:

DEC International and the DEC logo are trademarks, or registered trademarks of Dutch Environment Corporation BV in the Netherlands and/or other countries.